

THE COUNTRY'S LARGEST DISTRIBUTORS OF

Kempner

DISPLAY SHRINK MATERIALS AND MACHINERY

Semi-Automatic L Sealer and Shrink Tunnel



A constituent of the .com.pact
complete range of shrink wrap equipment



- exclusively available
- exceptional prices
- unsurpassable results
- built for all polyolefin films

The complete offer.

Our combined semi-automatic L sealer and shrink tunnel bridges the gap between manual and semi-automatic equipment, offering users state-of-the-art convenience with maximum output.

Standard features include solenoid lock-down with power take-off as well as lateral adjustment of the sealer with vertical adjustment of the tunnel conveyor, to permit perfect pack alignment.

Overall, our fundamental design objectives have been to offer the lowest possible purchase and running costs, whilst providing the highest quality output.

Semi-Automatic features

L Sealer

- Impulse seal with adjustable seal and dwell times
- Sideways adjustment to centre products into tunnel
- Fully controllable sealing cycle
- Powered variable product discharge conveyor
- Easy load film cradle with film brake and pin perforators
- Single ptfе coated seal blade with radiused corner
- Moveable on locking casters

Shrink Tunnel

- Fully re-circulating air chamber
- Adjustable conveyor height to match L Sealer
- Digital temperature control
- Automatic cool down and shut off cycle
- Adjustable conveyor speed
- Quiet running in operation
- Variable air flow

Semi-Automatic series specifications

Sealer Head dimensions	565 x 400mm
Maximum pack size	550 x 400 x 150mm
Maximum film width	600mm
Machine dimensions	2610 x 810 x 1570mm
Power supply	415/400v 3ph 20a/ph AC/50Hz
Power consumption	8 kw

Please seek guidance from S.Kempner Ltd, or their distributor, as to the maximum wrapped dimensions available on any unit.

As we have a quality policy objective of continuous improvement, we respectfully note that we have to reserve the right to amend specifications without notice.